



LVG

4G Outdoor Lighting LED Driver

Outdoor lighting LED Driver

Features

- Input Voltage: 120~277Vac
- Efficiency up to 92%
- Isolation dual-stage design, Flicker free
- Auxiliary 12V/0.2A optional
- No wiring required, easy to install and manage
- 4G full network access, remote single / group control, remote dimming, data analysis, fault warning
- IP67
- 5 years warranty

Power

75W 100W 150W 240W 320W

Model	Output Voltage (Vdc)	Output Current (A)	Output Power (W)	Efficiency	Power Factor	Dimension (L × W × H)(mm)	Surge DM/CM
ZH-LVG75R-56*	30-56	1.0-2.1	75	≥87%	≥95%	154 × 65 × 35	6KV/10KV
ZH-LVG100R-56*	30-56	1.4-2.8	100	≥90%	≥95%	154 × 65 × 35	6KV/10KV
ZH-LVG150R-56*	30-56	2.0-4.2	150	≥91%	≥95%	217 × 68 × 39	6KV/10KV
ZH-LVG240R-56*	30-56	3.0-6.6	240	≥92%	≥95%	217 × 68 × 39	6KV/10KV
ZH-LVG320R-56*	30-56	4.0-8.8	320	≥92%	≥95%	247 × 89 × 43	6KV/10KV

Note:

The default mode means no optional functions (basic model)

*=B means external 3 in 1 dimming function (0-10V/PWM/Resistance)

*=H means 0-10V dimming + auxiliary power supply (+12V) function