



FVP
High Power Strip Type Non-isolated LED Driver

Features

- Input voltage: 120~277Vac
- Efficiency up to 95%
- Non-isolated design, Flicker free
- Auxiliary 12V/0.2A optional
- 3-IN-1 Isolated dimming: 0-10V, PWM, Resistor
- IP67
- 5 years warranty

Certification



Power

400W 600W 720W
600W 800W 1000W 1200W

Model	Output Voltage (Vdc)	Output Current (A)	Output Power (W)	Efficiency	Power Factor	Dimension (L × W × H)(mm)	Surge DM/CM
ZH-FVP400R-400*	200-400	0.35-1.74	400	≥95%	≥95%	381 × 45 × 32	6KV/6KV
ZH-FVP600R-400*	200-400	0.35-2.6	600	≥95%	≥95%	433 × 45 × 32	6KV/6KV
ZH-FVP720R-400*	200-400	0.35-3.15	720	≥95%	≥95%	433 × 45 × 32	6KV/6KV

Model	Output Voltage (Vdc)	Output Current (A)	Output Power (W)	Efficiency	Power Factor	Dimension (L × W × H)(mm)	Surge DM/CM
ZH-FVP600RZ-360*	210-360	0.35-2.6	600	≥95%	≥95%	282 × 68 × 39	6KV/10KV
ZH-FVP800RZ-360*	210-360	2.2-3.3	800	≥95%	≥95%	375 × 68 × 39	6KV/10KV
ZH-FVP1000RZ-360*	210-360	2.7-4.2	1000	≥95%	≥95%	403 × 68 × 39	6KV/10KV
ZH-FVP1200RZ-360*	210-360	2.6-5.2	1200	≥95%	≥95%	487 × 68 × 39	6KV/10KV

Note:

The default mode means no optional functions (basic model)

*=B means external 3 in 1 dimming function (0-10V/PWM/Resistance)

*=H means 0-10V dimming + auxiliary power supply (+12V) function